


SMT Hardware

Cable Management & Grounding Clips

- Suitable for use with insulated cables with outer diameters Ø0.9 to Ø3mm and grounding braided coax cables.
- Cable clip can be soldered at same time as rest of board, reducing additional operation time required for mounting plastic clip types.
- Low profile & small footprint saves PCB space.








Materials Material:

Material: Finish: Copper Alloy Tin

Packaging

Format: Reel quantity: Tape & Reel Ø330mm reel, see table



Recommended PC Board Pattern

HOW TO ORDER

PART NO.	Α	B	C	D	COAX GROUNDING	CABLE RETENTION	REEL QUANTITY
\$8091-46R	5.00	4.00	1.35	0.70	Ø1.12mm	2 x Ø0.9mm	3,000
S8101-46R	5.00	4.00	1.50	0.80	RG178, RG179, RG316	2 x Ø1.0mm	3,000
S8111-46R	5.00	5.00	2.05	0.80	RG174, RG179, RG316	3 x Ø1.0mm, 2 x Ø1.5mm	1,500
S8121-46R	7.00	5.50	2.55	1.30	n/a	2 x Ø1.5mm, 1 x Ø2.0mm	1,300
S8131-46R	10.00	8.00	3.55	1.80	RG58	3 x Ø2.0mm, 1 x Ø3.0mm	800

All dimensions in mm.



www.harwin.com