



# CoolMOS™<sup>1)</sup> Power MOSFET with HiPerDyn™ FRED Buck and Boost Topologies

Electrically isolated back surface  
2500 V electrical isolation  
N-Channel Enhancement Mode  
Low  $R_{DS(on)}$ , high  $V_{DSS}$  MOSFET  
Ultra low gate charge



$I_{D25}$  = 15 A  
 $V_{DSS}$  = 600 V  
 $R_{DS(on)\ max}$  = 0.165 Ω



## MOSFET T

Symbol	Conditions	Maximum Ratings		
$V_{DSS}$	$T_{VJ} = 25^\circ\text{C}$	600	V	
$V_{GS}$		$\pm 20$	V	
$I_{D25}$	$T_C = 25^\circ\text{C}$	15	A	
$I_{D90}$	$T_C = 90^\circ\text{C}$	11	A	
$E_{AS}$ $E_{AR}$	single pulse repetitive } $I_D = 7.9 \text{ A}; T_C = 25^\circ\text{C}$	522 0.79	mJ mJ	
$dV/dt$	MOSFET dV/dt ruggedness $V_{DS} = 0 \dots 480 \text{ V}$	50	V/ns	

Symbol	Conditions	Characteristic Values		
		( $T_{VJ} = 25^\circ\text{C}$ , unless otherwise specified)	min.	typ.
$R_{DS(on)}$	$V_{GS} = 10 \text{ V}; I_D = 12 \text{ A}$		150	165
$V_{GS(th)}$	$V_{DS} = V_{GS}; I_D = 0.79 \text{ mA}$	2.5	3	3.5
$I_{DSS}$	$V_{DS} = 600 \text{ V}; V_{GS} = 0 \text{ V}$ $T_{VJ} = 25^\circ\text{C}$ $T_{VJ} = 125^\circ\text{C}$		10	1
$I_{GSS}$	$V_{GS} = \pm 20 \text{ V}; V_{DS} = 0 \text{ V}$			100
$C_{iss}$ $C_{oss}$	$V_{GS} = 0 \text{ V}; V_{DS} = 100 \text{ V}$ $f = 1 \text{ MHz}$	2000 100		pF pF
$Q_g$ $Q_{gs}$ $Q_{gd}$	$V_{GS} = 0 \text{ to } 10 \text{ V}; V_{DS} = 400 \text{ V}; I_D = 12 \text{ A}$	40 9 13	52	nC nC nC
$t_{d(on)}$ $t_r$ $t_{d(off)}$ $t_f$ $E_{on}$ $E_{off}$ $E_{rec\ off}$	$V_{GS} = 10 \text{ V}; V_{DS} = 400 \text{ V}$ $I_D = 12 \text{ A}; R_G = 3.3 \Omega$		12 5 50 5 tbd tbd tbd	ns ns ns ns mJ mJ mJ
$R_{thJC}$ $R_{thCH}$	with heat transfer paste	0.35	1.1	K/W K/W

<sup>1)</sup> CoolMOS™ is a trademark of Infineon Technologies AG.

## MOSFET T Source-Drain Diode

Symbol	Conditions	Characteristic Values		
		(T <sub>VJ</sub> = 25°C, unless otherwise specified)		
		min.	typ.	max.
I <sub>S</sub>	V <sub>GS</sub> = 0 V			12 A
V <sub>SD</sub>	I <sub>F</sub> = 12 A; V <sub>GS</sub> = 0 V	0.9	1.2	V
t <sub>rr</sub>		390		ns
Q <sub>RM</sub>	I <sub>F</sub> = 12 A; -di <sub>F</sub> /dt = 100 A/μs; V <sub>R</sub> = 400 V	7.5		μC
I <sub>RM</sub>		38		A

## Diode D (data for series connection)

Symbol	Conditions	Maximum Ratings				
V <sub>RRM</sub>	T <sub>VJ</sub> = 25°C to 150°C	600		V		
I <sub>F25</sub>	T <sub>C</sub> = 25°C	15		A		
I <sub>F90</sub>	T <sub>C</sub> = 90°C	8		A		
Symbol	Conditions	Characteristic Values				
		min.	typ.	max.		
V <sub>F</sub>						
I <sub>F</sub> = 15 A			T <sub>VJ</sub> = 25°C	2.50 V		
I <sub>F</sub> = 30 A				3.00 V		
I <sub>F</sub> = 15 A			T <sub>VJ</sub> = 150°C	2.00 A		
I <sub>F</sub> = 30 A				2.55 A		
I <sub>R</sub>			T <sub>VJ</sub> = 25°C	1 μA		
			T <sub>VJ</sub> = 150°C	0.08 mA		
I <sub>FSM</sub>			T <sub>VJ</sub> = 45°C	150 A		
rr" data-rs="2" style="vertical-align: middle; text-align: center;">I <sub>RM</sub>	I <sub>F</sub> = 20 A; V <sub>R</sub> = 100 V;		T <sub>VJ</sub> = 25°C	3 A		
	-di <sub>F</sub> /dt = 200 A/μs			35 ns		
R <sub>thJC</sub>				2.4 K/W		
R <sub>thJH</sub>			with heat transfer paste	0.8 K/W		

## Component

Symbol	Conditions	Maximum Ratings		
T <sub>VJ</sub>	operating	-55...+150		°C
T <sub>stg</sub>	storage	-55...+125		°C
V <sub>ISOL</sub>	I <sub>ISOL</sub> < 1 mA; 50/60 Hz	2500		V~
F <sub>c</sub>	mounting force with clip	20...120		N

Symbol	Conditions	Characteristic Values		
		min.	typ.	max.
C <sub>P</sub>	coupling capacity between shorted pins and mounting tab in the case	40		pF
d <sub>S</sub> , d <sub>A</sub>	pin - pin	1.7		mm
d <sub>S</sub> , d <sub>A</sub>	pin - backside metal	5.5		mm
Weight		9		g

## ISOPLUS i4™ Outline

